



Пластины для обработки канавок и отрезки серии FRIT

Пластины	Код заказа	Размеры							Державка	Сплав RU5025
		W	a	Dmax	r	IC	T	d		
 	FRIT R/L-12B050-00N	0,5	0	5	0,05	8,7	3	5	SFER/L-1010K12 SFER/L-1212K12 SFER/L-1212M12 SFER/L-1616M12 SFER/L-2020M12 SFER/L-2525M12	●
	FRIT R/L-12B070-00N	0,7	0	8	0,05	8,7	3	5		●
	FRIT R/L-12B100-00N	1,0	0	12	0,08	8,7	3	5		●
	FRIT R/L-12B150-00N	1,5	0	12	0,08	8,7	3	5		●
	FRIT R/L-12B200-00N	2,0	0	12	0,08	8,7	3	5		●
	FRIT R/L-12B050-16R	0,5	16	5	0,05	8,7	3	5		●
	FRIT R/L-12B070-16R	0,7	16	8	0,05	8,7	3	5		●
	FRIT R/L-12B100-16R	1,0	16	12	0,08	8,7	3	5		●
	FRIT R/L-12B150-16R	1,5	16	12	0,08	8,7	3	5		●
	FRIT R/L-12B200-16R	2,0	16	12	0,08	8,7	3	5		●
	FRIT R/L-12N050-00N	0,5	0	5	0,05	8,7	3	5		●
	FRIT R/L-12N070-00N	0,7	0	8	0,05	8,7	3	5		●
	FRIT R/L-12N100-00N	1,0	0	12	0,08	8,7	3	5		●
	FRIT R/L-12N150-00N	1,5	0	12	0,08	8,7	3	5		●
	FRIT R/L-12N200-00N	2,0	0	12	0,08	8,7	3	5		●
	FRIT R/L-12N050-20R	0,5	20	5	0,05	8,7	3	5		●
	FRIT R/L-12N070-20R	0,7	20	8	0,05	8,7	3	5		●
	FRIT R/L-12N100-20R	1,0	20	12	0,08	8,7	3	5		●
	FRIT R/L-12N150-20R	1,5	20	12	0,08	8,7	3	5		●
	FRIT R/L-12N200-20R	2,0	20	12	0,08	8,7	3	5		●
	FRIT R/L-16B100-00N	1,0	0	16	0,08	9,5	4	5	SFER/L-1010K16 SFER/L-1212K16 SFER/L-1212M16 SFER/L-1616M16 SFER/L-2020M16 SFER/L-2525M16	●
	FRIT R/L-16B150-00N	1,5	0	16	0,10	9,5	4	5		●
	FRIT R/L-16B200-00N	2,0	0	16	0,10	9,5	4	5		●
	FRIT R/L-16B250-00N	2,5	0	16	0,10	9,5	4	5		●
	FRIT R/L-16B300-00N	3,0	0	16	0,15	9,5	4	5		●
	FRIT R/L-16B100-16R	1,0	16	16	0,08	9,5	4	5		●
	FRIT R/L-16B150-16R	1,5	16	16	0,10	9,5	4	5		●
	FRIT R/L-16B200-16R	2,0	16	16	0,10	9,5	4	5		●
	FRIT R/L-16B250-16R	2,5	16	16	0,10	9,5	4	5		●
	FRIT R/L-16B300-16R	3,0	16	16	0,15	9,5	4	5		●
P - Сталь										★
M - Нержавеющая сталь										★
K - Чугун										★
N - Алюминий и цветные сплавы										
S - Титан и жаропрочные сплавы										

Пластины	Код заказа	Размеры							Державка	Сплав RU5025
		W	a	D _{max}	r	IC	T	d		
 	FRIT R/L-16N100-00N	1,0	0	16	0,08	9,5	4	5	SFER/L-1010K16 SFER/L-1212K16 SFER/L-1212M16 SFER/L-1616M16 SFER/L-2020M16 SFER/L-2525M16	●
	FRIT R/L-16N150-00N	1,5	0	16	0,10	9,5	4	5		●
	FRIT R/L-16N200-00N	2,0	0	16	0,10	9,5	4	5		●
	FRIT R/L-16N250-00N	2,5	0	16	0,10	9,5	4	5		●
	FRIT R/L-16N300-00N	3,0	0	16	0,15	9,5	4	5		●
	FRIT R/L-16N100-20R	1,0	20	16	0,08	9,5	4	5		●
	FRIT R/L-16N150-20R	1,5	20	16	0,10	9,5	4	5		●
	FRIT R/L-16N200-20R	2,0	20	16	0,10	9,5	4	5		●
	FRIT R/L-16N250-20R	2,5	20	16	0,10	9,5	4	5		●
	FRIT R/L-16N300-20R	3,0	20	16	0,15	9,5	4	5		●
P - Сталь										★
M - Нержавеющая сталь										★
K - Чугун										★
N - Алюминий и цветные сплавы										
S - Титан и жаропрочные сплавы										